

Colle

680-250ML-LOCTITE - 680-250ML-LOCTITE

<https://www.123roulement.ca/lubrifiant-adhesif/adhesif/colle/680-250ml-loctite>

TITRE	Anaérobie
DESCRIPTION	Viscosité moyenne, haute résistance
NOM	LOCTITE 680
CONDITIONNEMENT	11,250 ml
APPROBATION*	7

Description

LOCTITE 680 is a green, high strength, methacrylate ester acrylic liquid designed for the bonding of cylindrical fitting parts, particularly where low viscosity is required. The product prevents loosening and leakage from shock and vibration. It provides robust curing performance. It works on active metals (e.g. mild steel) and on passive substrates (e.g. stainless steel and plated surfaces).

Avantages

Low viscosity provides robust curing performance. Cures white, carbon in the absence of air between close fitting cylindrical surfaces. Offers high temperature performance and oil tolerance. Resistant to surface contamination from various oils. Certified to ANSI/ISO Standard for use in commercial and residential potable water systems not exceeding +175.0 °F (+82 °C).

Caractéristiques

High strength, methacrylate ester acrylic liquid designed for the bonding of cylindrical fitting parts, particularly where low viscosity is required.



CARACTÉRISTIQUES PRODUIT

Marque	LOCTITE
N° Ean13	5010266011165
Type	FIXATION ROULEMENT
Poids	325 g
Conditionnement	1
Utilisation	Anaérobie

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE