

Roulement conique 32306-CR-JTEKT - 32306-CR-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/32306-cr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)						Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ¹⁾				
d	D	T	B	C	r ₁ min.	r ₁ max.	C _r	C _{0r}	Grease lub.		Oil lub.			
30	72	28.75	27	23	1.5	1.5	80.0	93.8	6 000	8 000	32306CR			
Dimension series to ISO955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)						Constant e	Axial load factors		(Refer. 1) Mass (kg)			
		d ₁ min.	d ₂ max.	D ₁ max.	D ₂ min.	S ₁ min.	S ₂ min.		r ₁ max.	r ₂ max.		Y ₁	Y ₀	
5FD	22.0	38.5	37	63.5	54	68	3	5.5	1.5	1.5	0.55	1.10	0.60	0.610

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952400754
Diam. intérieur	30 mm
Diam. extérieur	72 mm
Épaisseur	28.75 mm
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE