


## Roulement conique 30209-XR-JTEKT - 30209-XR-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/30209-xr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>					
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.						
45	85	20.75	19	15	69.4	81.5	4 600	6 100	30209XR					
Dimension series to ISO95 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)												
		d <sub>1</sub> min.	d <sub>2</sub> max.	D <sub>1</sub> min.	D <sub>2</sub> min.	S <sub>1</sub> min.	S <sub>2</sub> min.	r <sub>1</sub> min.	r <sub>2</sub> min.	Constant e	Axial load factors Y <sub>1</sub>	Axial load factors Y <sub>0</sub>	(Refer. 1) Mass (kg)	
—	21.1	53.5	54	76.5	71	80	4	5.5	1.5	1.5	0.55	1.10	0.60	0.500

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952404998
Diam. intérieur	45 mm
Diam. extérieur	85 mm
Épaisseur	20.75 mm
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE