


## Roulement conique T2ED070-JTEKT - T2ED070-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/t2ed070-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>90</sub>	C <sub>100</sub>	Grease lub.	Oil lub.	
70	130	43	42	35	3	2.5	233	319	3 000	4 000	T2ED070

Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1</sub> min.	d <sub>2</sub> max.	D <sub>1</sub> min.	D <sub>2</sub> max.	S <sub>1</sub> min.	S <sub>2</sub> max.	r <sub>3</sub> min.	r <sub>4</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
2ED	30.2	84	81	118	111	123	1	1	2.5	2	0.33	1.80	0.99	2.48

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	4549250067310
Diam. intérieur	70 mm
Diam. extérieur	130 mm
Épaisseur	43 mm
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE