


## Roulement conique 30315-DJR-JTEKT - 30315-DJR-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/30315-djr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>					
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.						
75	160	40	37	26	213	254	2 100	2 900	30315DJR					
Dimension series to ISO355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)						Constant e	Axial load factors		(Refer. 1) Mass (kg)			
		d <sub>1</sub> min.	d <sub>2</sub> max.	D <sub>1</sub> min.	D <sub>2</sub> min.	S <sub>1</sub> min.	S <sub>2</sub> min.		r <sub>1</sub> max.	r <sub>2</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>	
7GB	49.9	89	91	148	127	151	6	14	2.5	2	0.83	0.73	0.40	3.45

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952409290
Diam. intérieur	75 mm
Diam. extérieur	160 mm
Épaisseur	40 mm
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE