

Roulement conique 30316-R-JTEKT - 30316-R-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/30316-r-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ¹⁾					
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
80	170	42.5	39	33	3	2.5	277	330	2 300	3 100	30316R			
Dimension series to ISO955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _α min.	d _α max.	D _α min.	D _α max.	S _α min.	S _α max.	r _α min.	r _α max.		Y ₁	Y ₀		
—	33.9	94	102	158	148	159	4	9.5	2.5	2	0.35	1.73	0.95	4.26

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	4549250122231
Diam. intérieur	80 mm
Diam. extérieur	170 mm
Épaisseur	42.5 mm
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE