

## Roulement conique 30322-JR-JTEKT - 30322-JR-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/30322-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>					
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.						
110	240	54.5	50	42	481	590	1 600	2 100	30322JR					
Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)						Constant e	Axial load factors		(Refer. 1) Mass (kg)			
		d <sub>1</sub> min.	d <sub>2</sub> max.	D <sub>1</sub> min.	D <sub>2</sub> max.	S <sub>1</sub> min.	S <sub>2</sub> max.		r <sub>1</sub> min.	r <sub>2</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>	
20B	46.3	128	141	226	206	222	8	12.5	3	2.5	0.35	1.74	0.96	11.4

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	4549250122477
Diam. intérieur	110 mm
Diam. extérieur	240 mm
Épaisseur	54.5 mm
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE