

Roulement conique 30324-JR-JTEKT - 30324-JR-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/30324-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



| Boundary dimensions (mm) | | | | | Basic load ratings (kN) | | | | Limiting speeds (min ⁻¹) | | Bearing No. ¹⁾ |
|--------------------------|-----|------|----|----|-------------------------|-----------------|-----------------|------------------|--------------------------------------|----------|---------------------------|
| d | D | T | B | C | C _r | C _{0r} | C ₉₀ | C ₁₀₀ | Grease lub. | Oil lub. | |
| 120 | 260 | 59.5 | 55 | 46 | 569 | 714 | 1 500 | 2 000 | | | 30324JR |

| Dimension series to ISO 355 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) | | | | | | | | | | Constant e | Axial load factors | | (Refer. 1) Mass (kg) |
|--|--------------------|--------------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|------------|--------------------|----------------|----------------------|
| | | d ₁ min. | d ₁ max. | D ₁ min. | D ₁ max. | S ₁ min. | S ₁ max. | r ₁ min. | r ₁ max. | r ₂ min. | r ₂ max. | | Y ₁ | Y ₀ | |
| 2GB | 50.2 | 138 | 152 | 246 | 221 | 239 | 10 | 13.5 | 3 | 2.5 | 0.35 | 1.74 | 0.96 | 14.5 | |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952411439 |
| Diam. intérieur | 120 mm |
| Diam. extérieur | 260 mm |
| Épaisseur | 59.5 mm |
| Conditionnement | 1 |

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE