


## Roulement conique 32972-JR-JTEKT - 32972-JR-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/32972-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>					
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.						
360	480	76	76	57	1 080	2 400	560	740	32972JR					
Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)												
		d <sub>1</sub> min.	d <sub>2</sub> max.	D <sub>1</sub> min.	D <sub>2</sub> min.	S <sub>1</sub> min.	S <sub>2</sub> min.	r <sub>1</sub> max.	r <sub>2</sub> max.	Constant e	Axial load factors Y <sub>1</sub>	Axial load factors Y <sub>0</sub>	(Refer. 1) Mass (kg)	
4FD	96.2	378	379	466	438	466	12	19	3	2.5	0.46	1.31	0.72	37.1

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952412122
Diam. intérieur	360 mm
Diam. extérieur	480 mm
Épaisseur	76 mm
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE