

Roulement conique 32926-JR-JTEKT - 32926-JR-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/32926-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



| Boundary dimensions (mm) | | | | | Basic load ratings (kN) | | | | Limiting speeds (min ⁻¹) | | Bearing No. ¹⁾ | | | |
|--------------------------------------|--------------------|--------------------------|---------------------|---------------------|-------------------------|---------------------|---------------------|---------------------|--------------------------------------|------------|---------------------------|----------------|----------------------|------|
| d | D | T | B | C | C _r | C _{0r} | Grease lub. | Oil lub. | | | | | | |
| 130 | 180 | 32 | 32 | 25 | 2 | 1.5 | 200 | 368 | 1 900 | 2 500 | 32926JR | | | |
| Dimension series to ISO95 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) | | | | | | | | Constant e | Axial load factors | | (Refer. 1) Mass (kg) | |
| | | d ₁ min. | d ₁ max. | D ₁ min. | D ₁ max. | S ₁ min. | S ₁ max. | r ₁ min. | r ₁ max. | | Y ₁ | Y ₀ | | |
| 20C | 31.4 | 140 | 141 | 171 | 165 | 174 | 6 | 7 | 2 | 1.5 | 0.34 | 1.77 | 0.97 | 2.42 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 4549250125669 |
| Diam. intérieur | 130 mm |
| Diam. extérieur | 180 mm |
| Épaisseur | 32 mm |
| Conditionnement | 1 |
| Norme | Sans norme |

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE