

## Roulement conique T4DB160-JTEKT - T4DB160-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/t4db160-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>			
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	S <sub>1a</sub>	S <sub>1b</sub>	Grease lub.	Oil lub.				
160	220	32	30	23	3	3	225	379	1 500	2 000	T4DB160			
Dimension series to ISO955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	d <sub>2a</sub> min.	d <sub>2a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.		S <sub>1b</sub> min.	S <sub>1b</sub> max.		Y <sub>1</sub>
4DB	44.7	174	172	206	204	213	5	9	2.5	2.5	0.49	1.23	0.68	3.23

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952421216
Diam. intérieur	160 mm
Diam. extérieur	220 mm
Épaisseur	32 mm
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE