

## Roulement conique 32238-JR-JTEKT - 32238-JR-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/32238-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>				
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>0e</sub>	C <sub>0a</sub>	Grease lub.	Oil lub.					
190	340	97	92	75	5	4	1090	1740	1000	1300	32238JR				
Dimension series to ISO955 (Refer.1)	Load center (mm) a	Mounting dimensions (mm)										Constant e	Axial load factors		(Refer.1) Mass (kg)
		d <sub>1</sub> min.	d <sub>1</sub> max.	d <sub>2</sub> min.	d <sub>2</sub> max.	D <sub>1</sub> min.	D <sub>1</sub> max.	S <sub>1</sub> min.	S <sub>1</sub> max.	S <sub>2</sub> min.	S <sub>2</sub> max.		r <sub>1</sub> min.	r <sub>1</sub> max.	
4GD	81.9	212	216	322	286	323	12	22	4	3	0.44	1.38	0.76	36.6	

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952421537
Diam. intérieur	190 mm
Diam. extérieur	340 mm
Épaisseur	97 mm
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE