


Roulement conique 41126-41286-JTEKT - 41126-41286-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/41126-41286-jtekt>

Single-row tapered roller bearings
inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _{max.}	<i>r</i> ₁ max.	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.
28.575	72.626	24.608	24.257	17.462	1.6	1.6	61.8	60.5	6 100	8 100

Bearing No.		Load center (mm) <i>a</i>	Mounting dimensions (mm)						Constant <i>e</i>	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring		<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a max.	<i>r</i> _b max.		<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
41126	41286	20.7	41.5	36.5	61.0	68.0	1.6	1.6	0.60	1.00	0.55	0.295	0.177

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952425900
Diam. intérieur	28.575 mm
Diam. extérieur	72.626 mm
Épaisseur	24.608 mm
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE