

Roulement conique 16137-16284-JTEKT - 16137-16284-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/16137-16284-jtekt>

Single-row tapered roller bearings
inch series

Koyo



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|--------|--------|--------|--------|-------------|---------------|-------------------------|----------|--------------------------------------|----------|
| d | D | T | B | C | r max. | r_1 min. | C_r | C_{10} | Grease lub. | Oil lub. |
| 34.925 | 72.238 | 20.638 | 20.638 | 15.875 | 3.6 | 1.2 | 49.7 | 61.3 | 5 600 | 7 400 |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | | Constant | Axial load factors | | (Refer.) Mass (kg) | |
|-------------|------------|------------------|--------------------------|-------|-------|-------|---------------|---------------|----------|--------------------|-------|--------------------|------------|
| Inner ring | Outer ring | a | d_a | d_b | D_a | D_b | r_a max. | r_b max. | e | Y_1 | Y_2 | Inner ring | Outer ring |
| 16137 | 16284 | 16.6 | 46.5 | 40.5 | 63.0 | 67.0 | 3.6 | 1.2 | 0.40 | 1.49 | 0.82 | 0.236 | 0.144 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952426310 |
| Diam. intérieur | 34.925 mm |
| Diam. extérieur | 72.238 mm |
| Épaisseur | 20.638 mm |
| Conditionnement | 1 |

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE