

Roulement conique 65212-65500-JTEKT - 65212-65500-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/65212-65500-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _{max.}	<i>r</i> _{1 min.}	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.
53.975	127.000	44.450	44.450	34.925	3.6	3.2	208	269	3 300	4 400

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a max.	<i>r</i> _b max.	<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
65212	65500	35.2	77.0	71.0	107.0	119.0	3.6	3.2	0.49	1.23	0.68	1.78	1.02

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952427959
Diam. intérieur	53.975 mm
Diam. extérieur	127 mm
Épaisseur	44.45 mm
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE