



Roulement conique 5583R-5535-JTEKT - 5583R-5535-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/5583r-5535-jtekt>

Single-row tapered roller bearings
inch series 



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _{max.}	<i>r</i> ₁ _{min.}	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.
60.325	122.238	43.658	43.764	36.512	3.6	3.2	221	318	3 200	4 300

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	<i>a</i>	<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a _{max.}	<i>r</i> _b _{max.}	<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
5583R	5535	31.1	78.0	72.0	106.0	116.0	3.6	3.2	0.36	1.67	0.92	1.66	0.807

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952428376
Diam. intérieur	60.325 mm
Diam. extérieur	122.238 mm
Épaisseur	43.658 mm
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE