


## Roulement conique 5584R-5535-JTEKT - 5584R-5535-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/5584r-5535-jtekt>

Single-row tapered roller bearings  
inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> <sub>max.</sub>	<i>r</i> <sub>1</sub> <sub>min.</sub>	<i>C</i> <sub>r</sub>	<i>C</i> <sub>10</sub>	Grease lub.	Oil lub.
63.500	122.238	43.658	43.764	36.512	3.6	3.2	221	318	3 200	4 300

Bearing No.		Load center (mm) <i>a</i>	Mounting dimensions (mm)						Constant <i>e</i>	Axial load factors		(Refer to)	
Inner ring	Outer ring		<i>d</i> <sub>a</sub>	<i>d</i> <sub>b</sub>	<i>D</i> <sub>a</sub>	<i>D</i> <sub>b</sub>	<i>r</i> <sub>a</sub> <sub>max.</sub>	<i>r</i> <sub>b</sub> <sub>max.</sub>		<i>Y</i> <sub>1</sub>	<i>Y</i> <sub>2</sub>	Inner ring	Outer ring
5584R	5535	31.1	61.0	75.0	106.0	116.0	3.6	3.2	0.36	1.67	0.92	1.56	0.807

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952428499
Diam. intérieur	63.5 mm
Diam. extérieur	122.238 mm
Épaisseur	43.658 mm
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE