


Roulement conique 655-653-JTEKT - 655-653-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/655-653-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _{max.}	<i>r</i> ₁ min.	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.
69.850	146.050	41.275	41.275	31.750	3.6	3.2	208	301	2 600	3 400

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer.) Mass (kg)		
Inner ring	Outer ring	<i>a</i>	<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a max.	<i>r</i> _b max.	<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
655	653	33.4	88.0	82.0	131.0	139.0	3.6	3.2	0.41	1.47	0.81	2.35	0.891

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952428857
Diam. intérieur	69.85 mm
Diam. intérieur	2 3/4" inch
Diam. extérieur	146.05 mm
Diam. extérieur	5 3/4" inch
Epaisseur	41.275 mm
Epaisseur	1 5/8" inch
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE