

Roulement conique 835R-832-JTEKT - 835R-832-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/835r-832-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _{max.}	<i>r</i> ₁ _{max.}	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.
69.850	168.275	53.975	56.383	41.275	3.6	3.2	344	467	2 300	3 100

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a _{max.}	<i>r</i> _b _{max.}	<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
835R	832	35.0	91.0	84.0	149.0	155.0	3.6	3.2	0.30	2.00	1.10	4.32	1.72

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952428871
Diam. intérieur	69.85 mm
Diam. extérieur	168.275 mm
Épaisseur	53.975 mm
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE