


## Roulement conique 567A-563-JTEKT - 567A-563-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/567a-563-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



| Boundary dimensions (mm) |          |          |          |          |                          |                            | Basic load ratings (kN) |                        | Limiting speeds (min <sup>-1</sup> ) |          |
|--------------------------|----------|----------|----------|----------|--------------------------|----------------------------|-------------------------|------------------------|--------------------------------------|----------|
| <i>d</i>                 | <i>D</i> | <i>T</i> | <i>B</i> | <i>C</i> | <i>r</i> <sub>max.</sub> | <i>r</i> <sub>1</sub> min. | <i>C</i> <sub>r</sub>   | <i>C</i> <sub>10</sub> | Grease lub.                          | Oil lub. |
| 71.438                   | 127.000  | 36.512   | 36.170   | 28.575   | 3.6                      | 3.2                        | 156                     | 226                    | 3 000                                | 4 000    |

| Bearing No. |            | Load center (mm) | Mounting dimensions (mm) |                       |                       |                       |                            |                            | Constant | Axial load factors    |                       | (Refer.) Mass (kg) |            |
|-------------|------------|------------------|--------------------------|-----------------------|-----------------------|-----------------------|----------------------------|----------------------------|----------|-----------------------|-----------------------|--------------------|------------|
| Inner ring  | Outer ring | <i>a</i>         | <i>d</i> <sub>a</sub>    | <i>d</i> <sub>b</sub> | <i>D</i> <sub>a</sub> | <i>D</i> <sub>b</sub> | <i>r</i> <sub>a</sub> max. | <i>r</i> <sub>b</sub> max. | <i>e</i> | <i>Y</i> <sub>1</sub> | <i>Y</i> <sub>2</sub> | Inner ring         | Outer ring |
| 567A        | 563        | 28.6             | 86.0                     | 80.0                  | 112.0                 | 120.0                 | 3.6                        | 3.2                        | 0.36     | 1.65                  | 0.91                  | 1.19               | 0.648      |

### CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | JTEKT         |
| N° Ean13        | 3663952428901 |
| Diam. intérieur | 71.438 mm     |
| Diam. extérieur | 127 mm        |
| Épaisseur       | 36.512 mm     |
| Conditionnement | 1             |

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE