


## Roulement conique

### HM813849-HM813811-JTEKT - HM813849-HM813811-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/hm813849-hm813811-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> <sub>max.</sub>	<i>r</i> <sub>1</sub> min.	<i>C</i> <sub>r</sub>	<i>C</i> <sub>10</sub>	Grease lub.	Oil lub.
71.438	127.000	36.512	36.512	26.988	3.6	1.6	166	235	3 000	4 000

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Con-stant	Axial load factors		(Refer.) Mass (kg)		
Inner ring	Outer ring	<i>a</i>	<i>d</i> <sub>a</sub>	<i>d</i> <sub>b</sub>	<i>D</i> <sub>a</sub>	<i>D</i> <sub>b</sub>	<i>r</i> <sub>a</sub> max.	<i>r</i> <sub>b</sub> max.	<i>e</i>	<i>Y</i> <sub>1</sub>	<i>Y</i> <sub>2</sub>	Inner ring	Outer ring
HM813849	HM813811	32.9	89.0	81.9	113.0	121.0	3.6	1.6	0.50	1.20	0.66	1.28	0.622

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952428918
Diam. intérieur	71.438 mm
Diam. intérieur	2 13/16" inch
Diam. extérieur	127 mm
Diam. extérieur	5" inch
Epaisseur	36.512 mm
Epaisseur	1 7/16" inch
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE