


## Roulement conique 756A-752-JTEKT - 756A-752-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/756a-752-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
$d$	$D$	$T$	$B$	$C$	$r$ max.	$r_1$ min.	$C_r$	$C_{10}$	Grease lub.	Oil lub.
79.375	161.925	47.625	48.260	38.100	7.9	3.2	273	391	2 400	3 200

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	$a$	$d_a$	$d_b$	$D_a$	$D_b$	$r_a$ max.	$r_b$ max.	$e$	$Y_1$	$Y_2$	Inner ring	Outer ring
756A	752	35.5	106.0	91.0	144.0	150.0	7.9	3.2	0.34	1.76	0.97	2.95	1.59

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952429267
Diam. intérieur	79.375 mm
Diam. extérieur	161.925 mm
Épaisseur	47.625 mm
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE