


Roulement conique 760-752-JTEKT - 760-752-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/760-752-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _{max.}	<i>r</i> ₁ _{min.}	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.
90.488	161.925	47.625	48.280	38.100	3.6	3.2	273	391	2 400	3 200

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer.) Mass (kg)		
Inner ring	Outer ring	<i>a</i>	<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a _{max.}	<i>r</i> _b _{max.}	<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
760	752	35.5	107.0	101.0	144.0	150.0	3.6	3.2	0.34	1.76	0.97	2.42	1.59

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952429748
Diam. intérieur	90.488 mm
Diam. extérieur	161.925 mm
Épaisseur	47.625 mm
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE