

## Roulement conique L521949R-L521910-JTEKT - L521949R-L521910-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/l521949r-l521910-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



| Boundary dimensions (mm) |         |        |        |        |                     |                       | Basic load ratings (kN) |          | Limiting speeds (min <sup>-1</sup> ) |          |
|--------------------------|---------|--------|--------|--------|---------------------|-----------------------|-------------------------|----------|--------------------------------------|----------|
| $d$                      | $D$     | $T$    | $B$    | $C$    | $r$ <sub>max.</sub> | $r_1$ <sub>min.</sub> | $C_r$                   | $C_{10}$ | Grease lub.                          | Oil lub. |
| 107.950                  | 146.050 | 21.432 | 21.432 | 16.670 | 1.6                 | 1.6                   | 86.4                    | 167      | 2 300                                | 3 100    |

  

| Bearing No. |            | Load center (mm) | Mounting dimensions (mm) |       |       |       |                       | Constant              | Axial load factors |       | (Refer) |            |            |
|-------------|------------|------------------|--------------------------|-------|-------|-------|-----------------------|-----------------------|--------------------|-------|---------|------------|------------|
| Inner ring  | Outer ring | $a$              | $d_a$                    | $d_b$ | $D_a$ | $D_b$ | $r_a$ <sub>max.</sub> | $r_b$ <sub>max.</sub> | $e$                | $Y_1$ | $Y_2$   | Inner ring | Outer ring |
| L521949R    | L521910    | 26.2             | 116.0                    | 114.0 | 136.0 | 141.0 | 1.6                   | 1.6                   | 0.39               | 1.53  | 0.84    | 0.665      | 0.325      |

### CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | JTEKT         |
| N° Ean13        | 3663952430065 |
| Diam. intérieur | 107.95 mm     |
| Diam. extérieur | 146.05 mm     |
| Épaisseur       | 21.432 mm     |
| Conditionnement | 1             |

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE