

## Roulement conique 48684-48620-JTEKT - 48684-48620-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/48684-48620-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> <sub>max.</sub>	<i>r</i> <sub>1</sub> min.	<i>C</i> <sub>r</sub>	<i>C</i> <sub>10</sub>	Grease lub.	Oil lub.
142.875	200.025	41.275	39.688	34.130	7.9	3.3	246	491	1 700	2 200

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer) Mass (kg)		
Inner ring	Outer ring	<i>a</i>	<i>d</i> <sub>a</sub>	<i>d</i> <sub>b</sub>	<i>D</i> <sub>a</sub>	<i>D</i> <sub>b</sub>	<i>r</i> <sub>a</sub> max.	<i>r</i> <sub>b</sub> max.	<i>e</i>	<i>Y</i> <sub>1</sub>	<i>Y</i> <sub>2</sub>	Inner ring	Outer ring
48684	48620	38.4	166.0	151.0	185.0	193.0	7.9	3.3	0.34	1.78	0.98	2.43	1.38

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952431703
Diam. intérieur	142.875 mm
Diam. intérieur	5 5/8" inch
Diam. extérieur	200.025 mm
Diam. extérieur	7 7/8" inch
Epaisseur	41.275 mm
Epaisseur	1 5/8" inch
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE