

Roulement à aiguilles 16MKM2216-JTEKT - 16MKM2216-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-aiguilles/aiguilles/16mkm2216-jtekt>

Drawn cup needle roller bearings Koyo

| Boundary dimensions (mm) | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | Bearing No. ²⁾ |
|--------------------------|----|----|-------------------------|-----------------|--------------------------------------|---------------------------|
| F _w | D | C | C _r | C _{0r} | Oil lub. | |
| 16 | 22 | 16 | 13.3 | 10.7 | 15.1 | 22 000 |

| Full complement type | | Recommended dimensions (mm) | | | | Refer. Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|-----------------------------|--------|-----------------|-----------------|
| With open ends | With closed end | Shaft dia. (f6) min. | max. | Housing bore dia. (N7) min. | max. | With open ends | With closed end |
| — | — | 15.989 | 16.000 | 21.972 | 21.993 | 15 | 17 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952470337 |
| Diam. intérieur | 16 mm |
| Diam. extérieur | 22 mm |
| Épaisseur | 16 mm |
| Poids | 17 g |
| Conditionnement | 1 |

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE