

## Roulement à aiguilles 20BM2612-JTEKT - 20BM2612-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-aiguilles/aiguilles/20bm2612-jtekt>

Drawn cup needle roller bearings Koyo

Full complement type  
With open ends

BM, BH-M

| Boundary dimensions (mm) |     |     | Basic load ratings (kN) |       | Limiting speeds (min <sup>-1</sup> ) |          | Bearing No. <sup>2)</sup> |                 |
|--------------------------|-----|-----|-------------------------|-------|--------------------------------------|----------|---------------------------|-----------------|
| $F_w$                    | $D$ | $C$ | $b$<br>min.             | $C_0$ | $C_{0e}$                             | Oil lub. | Caged type                |                 |
|                          |     |     |                         |       |                                      |          | With open ends            | With closed end |
| 20                       | 26  | 12  | 9.6                     | 10.6  | 20.4                                 | 6 300    |                           |                 |

  

| Full complement type |                 | Recommended dimensions (mm) |        |                                |        | (Refer.) Mass (g) |                 |
|----------------------|-----------------|-----------------------------|--------|--------------------------------|--------|-------------------|-----------------|
| With open ends       | With closed end | Shaft dia. (H6)<br>min.     | max.   | Housing bore dia. (H7)<br>min. | max.   | With open ends    | With closed end |
| 20BM2612             |                 | 19.987                      | 20.000 | 25.972                         | 25.993 | 15                | 17              |

### CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | JTEKT         |
| N° Ean13        | 3663952470771 |
| Diam. intérieur | 20 mm         |
| Diam. extérieur | 26 mm         |
| Épaisseur       | 12 mm         |
| Poids           | 15 g          |
| Conditionnement | 1             |

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE