

Roulement à aiguilles MKM2220-JTEKT - MKM2220-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-aiguilles/aiguilles/mkm2220-jtekt>

Drawn cup needle roller bearings Koyo

Boundary dimensions (mm)			Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ²⁾	
F_w	D	C	b min.	C_r	C_{10}	Oil lub.	Caged type	
							With open ends	With closed end
22	29	20	17.3	18.2	26.7	16 000		MKM2220

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	21.987	22.000	28.972	28.993	30	33

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952471228
Diam. intérieur	22 mm
Diam. intérieur	0.866" inch
Diam. extérieur	29 mm
Diam. extérieur	1.142" inch
Epaisseur	20 mm
Epaisseur	0.787" inch
Poids	33 g
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE