



Roulement à rouleaux NN3016K-JTEKT - NN3016K-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/rouleaux/nn3016k-jtekt>

Double-row cylindrical roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds (min ⁻¹)		Bearing No.	
d	D	B	r	F _w	C _r	C _{0r}	Grease lub.	Oil lub.	Cylindrical bore	Tapered bore
80	125	34	1.1	113	119	166	4 800	5 800	NN	NN3016K

		Mounting dimensions (mm)						(Refer.) Mass (kg)	
Cylindrical bore	Tapered bore	d _a		D _a		r _a		Cylindrical bore	Tapered bore
		min.	max.	min.	max.	min.	max.		
		86.5	—	—	118.5	114	1	1.55	1.50

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952473758
Diam. intérieur	80 mm
Diam. extérieur	125 mm
Épaisseur	34 mm
Poids	1500 g
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE