


## Roulement à rouleaux NN3080K-JTEKT - NN3080K-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/rouleaux/nn3080k-jtekt>

### Double-row cylindrical roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds (min <sup>-1</sup> )		Bearing No.	
<i>d</i>	<i>D</i>	<i>B</i>	<i>r</i> min.	<i>F<sub>w</sub></i>	<i>C<sub>10</sub></i>	<i>C<sub>90</sub></i>	Grease lub.	Oil lub.	Cylindrical bore	Tapered bore
400	600	148	5	548	2 030	4 140	700	850		<b>NN3080K</b>

		Mounting dimensions (mm)						(Refer.) Mass (kg)	
Cylindrical bore	Tapered bore	<i>d<sub>a</sub></i>		<i>D<sub>a</sub></i>		<i>r<sub>a</sub></i>		Cylindrical bore	Tapered bore
		min.	max.	min.	max.	min.	max.		
		420	—	580	552	4		146	141

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952474151
Diam. intérieur	400 mm
Diam. extérieur	600 mm
Épaisseur	148 mm
Poids	141000 g
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE