


Roulement à aiguilles 12NQ2410A-JTEKT - 12NQ2410A-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-aiguilles/aiguilles/12nq2410a-jtekt>

Machined ring needle roller bearings ————— **Koyo**
F_W 29 – 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F _w	d	D	B	C _r	C ₁₀	Oil lub.	Without inner ring	
12	—	24	9.8	—	5.9	6.3	35 000	12NQ2410A
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.	
With inner ring		d _i max.	D _i max.	r _a max.	Without inner ring	With inner ring		
		—	22	0.3	0.023	—	—	

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	4549250086960
Diam. intérieur	12 mm
Diam. extérieur	24 mm
Épaisseur	9.8 mm
Poids	23 g
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE