


## Roulement à aiguilles NQIS12-16-JTEKT - NQIS12-16-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-aiguilles/aiguilles/nqis12-16-jtekt>

Machined ring needle roller bearings ————— Koyo  
F<sub>w</sub> 29 – 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.	
F <sub>w</sub>	d	D	B	B <sub>1</sub>	C <sub>r</sub>	C <sub>10r</sub>	Oil lub.	Grease lub.	Without inner ring	
18	12	30	16	—	13.7	14.3	23 000	—	—	
Mounting dimensions (mm)					(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring					Without inner ring	With inner ring	—			
NQIS12/16					14	28	0.3	0.044	0.057	—

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3616060465535
Diam. intérieur	12 mm
Diam. extérieur	30 mm
Épaisseur	16 mm
Poids	57 g
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE