


Roulement à rouleaux NQI22-16-JTEKT - NQI22-16-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/rouleaux/nqi22-16-jtekt>

Machined ring needle roller bearings

F_w 29 – 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.	
F_w	d	D	B	B_s	r mm	C_r	C_{10}	Oil lub.	Without inner ring	
26	22	34	16	—	0.3	14.1	24.2	18 000	—	
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
		With inner ring	d_s min.	D_s max.	r_s max.	Without inner ring	With inner ring			
		NQI22/16	24	32	0.3	0.037	0.056			

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482477
Diam. intérieur	22 mm
Diam. extérieur	34 mm
Épaisseur	16 mm
Poids	56 g
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE