


Roulement à rouleaux NQ354514-JTEKT - NQ354514-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/rouleaux/nq354514-jtekt>

Machined ring needle roller bearings  **Koyo**
F_W 29 – 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F _w	d	D	B	C _r	C _{0r}	Oil lub.	Without inner ring	
35	—	45	14	16.9	29.0	13 000	NQ354514	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring			
	d _i min.	D _i max.	r _a max.	0.055	—			
	—	41	0.6					

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482859
Diam. intérieur	35 mm
Diam. extérieur	45 mm
Épaisseur	14 mm
Poids	55 g
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE