


## Roulement à rouleaux NA4906UU-JTEKT - NA4906UU-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/rouleaux/na4906uu-jtekt>

Machined ring needle roller bearings 

$F_w$  29 – 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
$F_w$	d	D	B	$B_1$	$r_{min}$	$C_r$	$C_{10}$	Oil lub.	Without inner ring
35	30	47	17	18	0.3	19.5	25.3	5 700	—
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring		$d_a$	$D_a$	$r_a$	Without inner ring	With inner ring			
NA4906UU		32	45	0.3	—	0.105	IRM303518		

[Note] 1) Limiting speeds of bearing number NA49...UU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482873
Diam. intérieur	30 mm
Diam. extérieur	47 mm
Épaisseur	17 mm
Poids	105 g
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE