


## Roulement à rouleaux NQ37-20-JTEKT - NQ37-20-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/rouleaux/nq37-20-jtekt>

### Machined ring needle roller bearings Koyo

$F_w$  29 – 37 mm

Without inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.
$F_w$	$d$	$D$	$B$	$r$ min.	$C_r$	$C_{10}$	Oil lub.		Without inner ring
37	32	47	20	0.3	26.0	45.1	13 000		<b>NQ37/20</b>
		Mounting dimensions (mm)			(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring		$d_a$ max.	$D_a$ max.	$r_a$ max.	Without inner ring	With inner ring			
		34	45	0.3	0.079	0.114			

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952482965
Diam. intérieur	37 mm
Diam. extérieur	47 mm
Épaisseur	20 mm
Poids	79 g
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE