


Roulement à rouleaux NQ40-15AD-JTEKT - NQ40-15AD-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/rouleaux/nq40-15ad-jtekt>

Machined ring needle roller bearings  **Koyo**
F_W 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F _w	d	D	B	C _r	C _{0r}	Oil lub.	Without inner ring	
40	—	50	15	—	21.0	35.1	12 000	NQ40/15AD
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring			
	d _a	D _a	r _a	—	—			
	max.	max.	max.	0.063	—			

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952483023
Diam. intérieur	40 mm
Diam. extérieur	50 mm
Épaisseur	15 mm
Poids	63 g
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE