


Roulement à rouleaux RNA49-48R-JTEKT - RNA49-48R-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/rouleaux/rna49-48r-jtekt>

Machined ring needle roller bearings

F_w 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F_w	d	D	B	C_r	C_{10}	Oil lub.	Without inner ring	
55	—	70	22	46.9	76.5	8 300	RNA49/48R	
Mounting dimensions (mm)				(roller) Mass (kg)		(roller) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring	—		
d_a	D_a	r_a		0.6	0.174			
max.	max.	max.						
—	66	0.6						

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952483481
Diam. intérieur	55 mm
Diam. extérieur	70 mm
Épaisseur	22 mm
Poids	174 g
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE