


## Roulement à rouleaux RNA49-48R-JTEKT - RNA49-48R-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/rouleaux/rna49-48r-jtekt>

### Machined ring needle roller bearings Koyo

$F_w$  29 – 37 mm

Without inner ring



| Boundary dimensions (mm) |     |     |     | Basic load ratings (kN) |                 | Limiting speeds <sup>1)</sup> (min <sup>-1</sup> ) |                    | Bearing No. |
|--------------------------|-----|-----|-----|-------------------------|-----------------|--|--------------------|-------------|
| $F_w$                    | $d$ | $D$ | $B$ | $C_r$                   | $C_{10}$        | Oil lub.   | Without inner ring |             |
| 55                       | —   | 70  | 22  | —                       | 46.9            | 76.5   | 8 300              | RNA49/48R   |
| Mounting dimensions (mm) |     |     |     | ( roller ) Mass (kg)    |                 | ( roller ) Applicable inner ring No.               |                    |             |
| With inner ring          |     |     |     | Without inner ring      | With inner ring | —  |                    |             |
| —                        |     |     |     | 66                      | 0.6             | 0.174  | —                  |             |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTÉRISTIQUES PRODUIT

|                 |               |
|-----------------|---------------|
| Marque          | JTEKT         |
| N° Ean13        | 3663952483481 |
| Diam. intérieur | 55 mm         |
| Diam. extérieur | 70 mm         |
| Épaisseur       | 22 mm         |
| Poids           | 174 g         |
| Conditionnement | 1             |

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE