


Roulement à rouleaux NA4910-JTEKT - NA4910-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/rouleaux/na4910-jtekt>

Machined ring needle roller bearings ————— Koyo
F_w 29 ~ 37 mm
With inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F _w	d	D	B	C _r	C _{0r}	Oil lub.	Without inner ring	
58	50	72	22	35.7	70.6	8 100	—	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring			
NA4910				54	68	0.191	0.298	IRM505822

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	4549250025891
Diam. intérieur	50 mm
Diam. intérieur	1.969" inch
Diam. extérieur	72 mm
Diam. extérieur	2.835" inch
Epaisseur	22 mm
Epaisseur	0.866" inch
Poids	298 g
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE