


Roulement à rouleaux RNA4912-JTEKT - RNA4912-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/rouleaux/rna4912-jtekt>

Machined ring needle roller bearings Koyo

F_w 29 – 37 mm

Without inner ring



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. |
|--------------------------|-----|--------------------------|-------|-------------------------|--------------------|--|------------------------------------|-------------|
| F_w | d | D | B | C_r | C_{10} | Oil lub. | Without inner ring | |
| 68 | 60 | 85 | 25 | 45.8 | 93.3 | 8 900 | RNA4912 | |
| | | Mounting dimensions (mm) | | | (Refer.) Mass (kg) | | (Refer.) Applicable inner ring No. | |
| With inner ring | | d_a | D_a | r_a | Without inner ring | With inner ring | | |
| | | 65 | 80 | 1 | 0.310 | 0.459 | IRM00825 | |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952483726 |
| Diam. intérieur | 68 mm |
| Diam. extérieur | 85 mm |
| Épaisseur | 25 mm |
| Poids | 310 g |
| Conditionnement | 1 |

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE