


## Roulement à rouleaux NA4914-JTEKT - NA4914-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/rouleaux/na4914-jtekt>

### Machined ring needle roller bearings

$F_w$  29 – 37 mm

With inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No.	
$F_w$	d	D	B	$C_r$	$C_{10}$	Oil lub.	Without inner ring		
80	70	100	30	86.4	157.0	5 700	—		
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				Without inner ring	With inner ring				
NA4914				75	95	1	0.483	0.733	IRM708030

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952483856
Diam. intérieur	70 mm
Diam. extérieur	100 mm
Épaisseur	30 mm
Poids	733 g
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE