


## Roulement conique 30230-JR-JTEKT - 30230R-JTEKT

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/30230r-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>					
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.						
150	270	49	45	38	483	664	1 300	1 800	30230JR					
Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)												
		d <sub>α</sub> min.	d <sub>β</sub> max.	D <sub>α</sub> max.	D <sub>β</sub> min.	S <sub>α</sub> min.	S <sub>β</sub> min.	r <sub>α</sub> max.	r <sub>β</sub> max.	Constant e	Axial load factors (Refer. 1)		Mass (kg)	
4GB	52.4	168	175	256	234	255	9	11	3	2.5	0.44	1.38	0.76	11.6

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	4549250258749
Diam. intérieur	150 mm
Diam. extérieur	270 mm
Épaisseur	49 mm
Poids	10500 g
Conditionnement	1
Norme	Sans norme

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE