


Douille à aiguilles BAM186-IKO - BAM186-IKO

<https://www.123roulement.ca/roulement-palier/roulement-aiguilles/douille/bam186-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
28.575 (1 1/8)	—	—	—	—	—	—	—	BAM 186	18.1	—	—
Boundary dimensions mm(inch)			Standard mounting dimensions mm				Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ^(*)	Assembled inner ring	
F _w	D	C	t ₁ Max	Shaft dia. h _s Max. Min.	Housing bore dia. J7 Max. Min.	Max. Min.	N	N	rpm	—	
28.575 1/8	34.925 1 3/8	9.52 3/8	2.8	28.575 28.562	34.939 34.914	6.330	8.910	13.000	—	—	

Note^(*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952173368
Diam. intérieur	28.58 mm
Diam. extérieur	34.93 mm
Épaisseur	9.52 mm
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE