


Douille à aiguilles BAM68-IKO - BAM68-IKO

<https://www.123roulement.ca/roulement-palier/roulement-aiguilles/douille/bam68-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained (Ref.) g
9.525 ($\frac{3}{8}$)	—	—	—	—	—	BAM 68	—	6.1	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽¹⁾	Assembled inner ring
F_w	D	C	Shaft dia. h_8	Housing bore dia. J_7	b_2	C	C_0	rpm		
9.525 $\frac{3}{8}$	14.288 $\frac{1}{2}$	12.70 500	1	9.525 Max.	9.516 Min.	14.298 14.280	4 190	4 560	40 000	—

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952173504
Diam. intérieur	9.53 mm
Diam. extérieur	14.29 mm
Épaisseur	12.7 mm
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE