


Douille à aiguilles BAM910-IKO - BAM910-IKO

<https://www.123roulement.ca/roulement-palier/roulement-aiguilles/douille/bam910-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g
14.288 ($\frac{9}{16}$)	—	—	—	—	—	BAM 910	10.8	—	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽¹⁾	Assembled inner ring
F_w	D	C	Shaft dia. ϕ		Housing bore dia. ϕ	C	C_0	rpm		
			h8 Max.	H7 Min.	J7 Max.	N Min.	N Min.			
14.288	19.050	15.881	14.288	14.277	19.062	19.041	7 050	9 910	30 000	—

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952173627
Diam. intérieur	14.29 mm
Diam. extérieur	19.05 mm
Épaisseur	15.88 mm
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE