

Rondelle de butée WS1730-IKO - WS1730-IKO

<https://www.123roulement.ca/accessoire/rondelle/rondelle-butee/ws1730-iko>

IKO
THRUST BEARINGS
Thrust Needle Roller Bearings

Shaft dia. mm	Identification number						
	Thrust needle roller bearing	Mass (Ref.) g	Thrust washer	Mass (Ref.) g	Inner ring	Outer ring	Mass (Ref.) g
17	NTB 1730	4.5	AS 1730	3.7	WS 1730	GS 1730	10.2

d	Boundary dimensions mm						Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm	
	D	D _w	s	B	r _s min ⁽¹⁾	C _i				C ₀
17	30	2	1	2.75	0.3	20	28	9 320	32 900	11 000

Notes: (1) Minimum allowable value of chamfer dimension r
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 25% of this value is allowable.

CARACTÉRISTIQUES PRODUIT

Marque	IKO
N° Ean13	3663952298863
Diam. intérieur	17 mm
Diam. extérieur	30 mm
Épaisseur	2.75 mm
Matière	ACIER
Poids	10 g
Conditionnement	1

contact@123roulement.ca

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE