

## Roulement conique 2474-2420-TIMKEN - 2474-2420-TIMKEN

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/2474-2420-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**

Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> Y	Dynamic <sup>(3)</sup> C <sub>2</sub>	Factor <sup>(4)</sup> X	Static C <sub>0</sub>	Inner	Outer	
mm	mm	mm	N		N		N			
28.575	68.262	22.225	6760	1.31	17500	16000	1.72	23200	2474	2420
1.1250	2.6875	0.8750	15500		3940	2200		16500		

  

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage	G <sub>1</sub>	G <sub>2</sub>		C <sub>3</sub>
Width B	Width C	ER. Dr. α <sup>(1)</sup>	Max Shaft Fillet Radius R <sub>1</sub>	Backing Shoulder Dia. d <sub>1</sub>	Max Housing Fillet Radius r <sup>(2)</sup>	Backing Shoulder Dia. D <sub>1</sub>	A <sub>1</sub> <sup>(3)</sup>	A <sub>2</sub> <sup>(4)</sup>	A <sub>3</sub> <sup>(5)</sup>				kg	
22.812	17.462	-4.4	0.8	35.0	36.8	1.5	63.0	60.0	0.9	0.3	10.0	10.5	0.062	0.42
0.9015	0.6875	-0.26	0.03	1.38	1.42	0.06	2.49	2.38	0.03	0.01				0.90

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952307015
Diam. intérieur	28.58 mm
Diam. intérieur	1 1/8" inch
Diam. extérieur	68.26 mm
Diam. extérieur	2 11/16" inch
Epaisseur	22.23 mm
Epaisseur	7/8" inch
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE