

## Roulement conique 2580-2530-TIMKEN - 2580-2530-TIMKEN

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/2580-2530-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • TYPE TS

**TYPE TS**

Bearing Dimensions			Load Ratings						Part Number			
Bore d	O.D. D	Width T	Dynamic <sup>(1)</sup> C <sub>1</sub>	Static <sup>(2)</sup> C <sub>0</sub>	Dynamic <sup>(3)</sup> C <sub>2</sub>	Static <sup>(4)</sup> C <sub>0</sub>	Factor <sup>(5)</sup> K	Inner	Outer			
mm	mm	mm	N	N	N	N						
31.750	66.421	25.400	83700	18500	2.37	2.15	21700	10200	2.14	94000	2580	2530
1.250	2.6150	1.0000					4800	2200		372000		

  

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					G <sub>1</sub>	G <sub>2</sub>	C <sub>3</sub>		
Width B	Width C	ER. Dr. α <sup>(1)</sup>	Max. Shaft Fillet Radius R <sup>(2)</sup>	Backing Shoulder Dia. d <sub>1</sub>	Max. Housing Fillet Radius r <sup>(3)</sup>	Backing Shoulder Dia. D <sub>1</sub>	Cage A <sub>1</sub> <sup>(4)</sup>	A <sub>2</sub> <sup>(5)</sup>	A <sub>3</sub> <sup>(6)</sup>				A <sub>4</sub> <sup>(7)</sup>	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kg
25.267	26.636	-0.4	0.8	37.5	38.5	0.8	62.5	59.9	0.8	0.8	25.6	9.6	0.9008	0.41
0.9983	0.8125	-0.34	0.03	1.48	1.52	0.03	2.46	2.38	0.03	0.04				0.91

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952308524
Diam. intérieur	31.75 mm
Diam. extérieur	66.42 mm
Épaisseur	25.4 mm
Conditionnement	1

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE