

## Roulement conique 1674-1620-TIMKEN - 1674-1620-TIMKEN

<https://www.123roulement.ca/roulement-palier/roulement-rouleaux/conique/1674-1620-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE ROW • TYPE TS

**TYPE TS**

Bearing Dimensions			Load Ratings						Part Number		
Bore d	O.D. D	Width T	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> f	Dynamic <sup>(3)</sup> C <sub>0</sub>	Factor <sup>(4)</sup> K	Static C <sub>0</sub>	Inner	Outer		
mm	mm	mm	N		N		N				
31.623	66.675	20.638	3250	1.37	1.62	13000	8050	1.57	12000	1674	1620
1.250	2.625	0.8125	11500			3600	1950		13000		

  

Bearing Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing					Cage	G <sub>1</sub>	G <sub>2</sub>		C <sub>3</sub>
Width B	Width C	ER. Dr. a <sup>(1)</sup>	Max Shaft Fillet Radius R <sup>(2)</sup>	Backing Shoulder Dia. d <sub>1</sub>	Max Housing Fillet Radius r <sup>(3)</sup>	Backing Shoulder Dia. D <sub>1</sub>	A <sub>1</sub> <sup>(4)</sup>	A <sub>2</sub> <sup>(5)</sup>	A <sub>3</sub> <sup>(6)</sup>				A <sub>4</sub> <sup>(7)</sup>	
20.638	15.875	-5.3	1.5	37.8	35.5	1.5	61.0	58.0	1.5	1.1	16.6	6.7	0.9644	0.33
0.8125	0.6250	-0.21	0.06	1.46	1.56	0.06	2.40	2.28	0.06	0.05				0.72

### CARACTÉRISTIQUES PRODUIT

Marque	TIMKEN
N° Ean13	3663952309941
Diam. intérieur	31.62 mm
Diam. extérieur	66.68 mm
Épaisseur	20.64 mm
Poids	200 g
Conditionnement	1
Norme	Sans norme

[contact@123roulement.ca](mailto:contact@123roulement.ca)

+33 359 360 490

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE